



MK-1350 STEAM MAX VACUUM

PAROGENERATOR & USISIVAČ SA NEOGRANIČENOM AUTONOMIJOM
STEAM & VACUUM CLEANER WITH UNLIMITED AUTONOMY



uključeni dodaci - accessories included



Teh. karakteristike	specs	jedinica mera measure units	STEAM MAX VACUUM
napajanje	power supply	V-Hz	230-50
radni pritisak	working pressure	bar/psi	6/87
ukupna snaga	total power	W	3.000
snaga bojlera	boiler power	W	2.000
proizvodnja pare	steam production	g/min	110
jačina struje	power absorption	A	13
vreme pokretanja	start up time	min	5
zapremina bojlera	boiler capacity	liter/gallon	2/0,53
temperatura bojlera	boiler temperature	°C/°F	165/ 329
materijal bojlera	boiler material	type	inox AISI 304
regulacija izlaska pare	steam output regulation	type	ručna
regulacija izlaska vode	water output regulation	da/ne	ne
izlaz vode	water output	da/ne	da
izlaz deterdženta	detergent output	da/ne	da
zapremina rezervoara za vodu	water tank capacity	litar/gallon	5/1,32
zapremina rezervoara deterdž.	detergent tank capacity	litar/gallon	2/0,53
materijal kućišta	body material	vrsta	inox
neto težina	weight net	kg/lbs	26 + 7 / 57 + 15
dimenzije uređaja	machine dimension	d x š x v cm	36 x 52 x 100
dimenzije pakovanja	packaging dimension	d x š x v cm	58 x 39 x 96
težina pakovanja	packaging weight	kg/lbs	35 + 7 / 77 + 15
kutija pakovanja	packaging box	vrsta	karton
rezervoar otpadne vode	waste water tank capacity	litar/gallon	15/3,96
snaga usisavanja	vacuum power	W	1.000
vakuum	vacuum	kPa	24
filter usisivača	vacuum filter	vrsta	poliester
mokro & suvo	wet & dry	da/ne	da

